

RIG#3 TR-1 INVENTORY

Portable/ Mechanical Driven Rig

PRINCIPAL PARTICULARS

Type: Portable/Mechanical
Rating: 190 HP
Drilling Depth: 2625ft / 800m with 3 1/2" DP
Workover Depth: 4920ft / 1500m with 2-7/8" TBG

DRAWWORKS

Horsepower Rating: 200HP
Driven by: 1x PRO Diesel Engine
Transmission Type: ZF Transmissions
Drilling Line Diameter: 1"

MAST

Height: 41ft / 12.5m
Hook load: 110klbs / 50t @ 4 lines
Racking Capacity: 2625ft / 800m - 3 1/2" DP

SUBSTRUCTURE

Type: TKNK-1
Dimensions: 12x9ft / 3.6x2.75m
Adjustable Height: 4ft - 8.5ft / 1.25m - 2.6m
Setback Capacity: 175klbs / 80t
Casing Capacity: 175klbs / 80t

CARRIER

Type: DODGE AS900
Transmission: DODGE
Lifting Type: Hydraulics Lifts

ROTARY EQUIPMENTS

Rotary table type: TURKISH
Rotary table opening: 10"
Rotary Table capacity: 132klbs / 60t
Driven by: Drawwork's

TRAVELING EQUIPMENTS

Traveling Block: TURKISH
Block Capacity: 110klbs / 50t
Swivel Type: TURKISH
Swivel Capacity: 110klbs / 50t

RIG POWER SUPPLY

Generator#1 Type: AKSA AJD90
Generator#1 Rating: 90kVA / 72 kW
Generator#1 Voltage: 230/400V/50Hz

MUD SYSTEM

Mud Pumps: 1- BRN-1 duplex mud pump
Horsepower Rating: 630 HP
Power Pump: 2x CUMMINS V6 Diesel Engine
Shale Shaker: UPETROM Shaker
Mud Cleaner: UPETROM
Active Mud System: 550bbls

BOP EQUIPMENTS

UPETROM 21 1/4" 2K Single Ram BOP
UPETROM 21 1/4" 2K Drilling Spool
UPETROM 13 5/8" 5K Single Ram BOP
UPETROM 13 5/8" 5K Drilling Spool
UPETROM 9" 5K Annular BOP
13 5/8" 5K Riser Spool
13 5/8" 5K Rotating Control Device

TUBULAR

3 1/2" DP, 13.3 ppf - 80 ea
3 1/2" HWDP, 23.3 ppf - 5 ea
6 1/4" DC, 91 ppf - 6 ea
4 3/4" DC, 47 ppf - 8 ea
X-Overs
Stabilizers
Lifting Subs

VEHICLES

Hi-up (22 Ton Capacity)
Mitsubishi 4x4 Pick-up - 1 ea